



03.15.2009

ASW Series
Chilled -Hot Water Coils

**.022 SMOOTH BORE COPPER TUBING
CORRUGATED ALUMINUM FINNS
HEAVY ALUMINUM END PLATES
PRESSURE TESTED TO 450 LBS.
POLYMER DRAIN PAN
PITCHED DRAIN PAN FOR EASY
REMOVAL OF WATER**



Product Uncased Dimensions			
Model	Width "W"	Depth "D"	Height "H"
ASW24-A3662L	18"	21"	17-1/2"
ASW30-A3862L	18"	21"	19-1/2"
ASW36-A4862L	18"	21"	19-1/2"
ASW48-A4082L	21"	22"	21-1/2"
ASW60-A4082L	21"	22"	21-1/2"

Coil Specifications							
Model	Nom CAP	Nom CFM	Face Area	Rows	FPI	Circuits	Connect Size
ASW 24-A3662L	2	800	3.66	3	12	6	7/8"
ASW30-A3862L	2.5	1000	4.125	3	12	6	7/8"
ASW36-A4862L	3	1200	4.125	4	12	6	7/8"
ASW48-A4082L	4	1600	5.0	4	12	10	7/8"
ASW60-A4082L	5	2000	5.0	4	12	10	1 1/8"

**5-YEAR LIMITED WARRANTY AGAINST COIL LEAKAGE
5-YEAR LIMITED WARRANTY AGAINST DRAIN PAN BREAKAGE
1-YEAR LIMITED PARTS WARRANTY**